



50 CC SCOOTER RANGE


















- Low fuel consumption
- Mini GT comfort / Compact dimensions
- Excellent comfort thanks to the low saddle
- Helmet compartment for 2 demi-jet helmets with visor
- Maximum functionality thanks to the flat footboard and the fuel cap in the leg shield back plate


- Maximum respect for the environment and low fuel consumption
- Comfortable saddle adjustable to three different height positions
- Spacious helmet compartment, large enough to hold a full-face helmet





COLORS RANGE

NRG POWER



TYPHOON



FLY



ZIP



	NRG POWER	TYPHOON
	50 2S DD	50 2S
Engine	Single cylinder 2-stroke	Single cylinder 2-stroke
Engine capacity	49.4 cc	49.4 cc
Bore x Stroke	40 mm x 39.3 mm	40 mm x 39.3 mm
Power	3.3 kW -4.5 CV- at 7,250 rpm	3 kW -4.1 CV- at 6,500 rpm
Torque	4.7 Nm at 6,000 rpm	4.6 Nm at 6,000 rpm
Fuel system	Carburettor	Carburettor
Cooling system	Liquid	Air
Lubrication	Automatic mixer with throttle grip assist at engine running speed	Automatic mixer with throttle grip assist at engine running speed
Starter	Electric and kick starter	Electric and kick starter
Gearbox	CVT continuously variable transmission with torque server	CVT continuously variable transmission with torque server
Clutch	Automatic centrifugal dry clutch	Automatic centrifugal dry clutch
Frame	Single cradle structure in high resistance tubular steel	Single cradle structure in tubular steel with pressed reinforcements
Front suspension	Upside down hydraulic telescopic fork	Upside down hydraulic telescopic fork
Rear suspension	Hydraulic shock absorber	Hydraulic shock absorber
Front brake	Ø 220 mm disc with hydraulic control	Ø 220 mm disc with hydraulic control
Rear brake	Ø 175 mm disc with hydraulic control	Ø 140 mm drum
Front tyre	Tubeless 120/70 - 13"	Tubeless 120/80 - 12"
Rear tyre	Tubeless 140/60 - 13"	Tubeless 130/80 - 12"
Length/ Width/Wheelbase	1,790 mm / 750 mm / 1,280 mm	1,940 mm / 720 mm / 1,350 mm
Saddle height	810 mm	765 mm
Fuel tank capacity	6.7 litri	7 litri
Emissions compliance	EURO 2	EURO 2

All of the vehicles are ecological with European Community Emissions Compliance in observance of the atmospheric and sound pollution limits.

The company reserves the right to make technical and aesthetic changes at any time. Ride carefully, always wearing a helmet and suitable gear.

Always comply with the rules of the road and respect the environment. Read the operating and maintenance manual carefully. Always ask for original and approved spare parts in accordance with prevailing standards. See your Official Piaggio Dealership and authorised Retailers for a sure purchase and for guaranteed service support. With original Piaggio spare parts you can be certain of quality and they maintain the performance of your vehicle unaltered.

	FLY	ZIP
	50 4 S	50 4S (50 2S)*
Engine	Single cylinder, 4-stroke 2 valves	Single cylinder, 4-stroke, 2 valves (Single cylinder, 2-stroke)
Engine capacity	49.9 cc	49.9 cc (49.4 cc)
Bore x Stroke	39 mm x 41,8 mm	39 mm x 41.8 mm (40 mm x 39.3 mm)
Power	2.6 kW -3.5 CV- at 8,500 rpm	2.6 kW -3.5 CV- a 8,500 rpm (3.3 kW -4.5 CV- a 6,700 rpm)
Torque	3.3 Nm at 6,500 rpm	3.6 Nm a 6,500 rpm (4.3 Nm a 6,500 rpm)
Fuel system	Carburettor	Carburettor
Cooling system	Air	Air
Lubrication	Wet sump	Wet sump (Automatic mixer with throttle grip assist at engine running speed)
Starter	Electric and kick starter	Electric and kick starter
Gearbox	CVT with torque server	CVT continuously variable transmission with torque server
Clutch	Automatic centrifugal dry clutch	Automatic centrifugal dry clutch
Frame	Single cradle structure in tubular steel with pressed reinforcements	Single cradle structure in high resistance tubular steel
Front suspension	Hydraulic telescopic fork	Hydraulic telescopic fork
Rear suspension	Hydraulic monoshock absorber	Hydraulic shock absorber
Front brake	Ø 220 mm disc with hydraulic control	Ø 175 mm disc with hydraulic control
Rear brake	Ø 140 mm drum	Ø 110 mm drum
Front tyre	Tubeless 120/70 - 12"	Tubeless 100/80 - 10"
Rear tyre	Tubeless 120/70 - 12"	Tubeless 120/70 - 10"
Length/ Width/Wheelbase	1,870 mm / 705 mm / 1,345 mm	1,700 mm / 680 mm / 1,200 mm
Saddle height	760 mm	Adjustable: 750 mm - 765 mm - 780 mm
Fuel tank capacity	7 Litres (including 1.5 litre reserve)	7.3 Litres
Emissions compliance	EURO 2	EURO 2

